


20-40  
BAR



AF COMPRESSORS

af  
RANGE

OIL FREE  
PISTON PET  
COMPRESSORS



WWW.AFCOMPRESSORS.COM



# RANGE OF CAPACITIES

## HIGH PRESSURE OIL FREE AIR COMPRESSORS




**SIMPLE & EFFICIENT DESIGN**



**LOW ENERGY CONSUMPTION**



**LOW MAINTENANCE COSTS**



MODEL	Capacity m <sup>3</sup> /h FAD	Capacity CFM	Installed power kW
M 2 XS	150	88	30
M 2 S	185	109	37
M 2 A	225	132	45
CE 24 XS	315	185	55
CE 24 S	425	250	75
CE 24 A	510	300	90
CE 24 B	600	353	110
CE 24 C	700	412	132
L 3 A	770	453	132
L 4	800	471	132
CE 46 S	910	536	160
L 4 A	975	574	160
CE 46 A	1160	683	200
L 5 XS	1260	742	200
L 5 S	1330	783	220
CE 46 C	1450	853	250
L 5 A	1530	901	250
L 5 B	1680	989	280
L 6	1760	1036	280
L 6 A	1940	1142	315
CE 68 A	2100	1236	355
L 6 B	2170	1277	355
L 7	2330	1371	400
L 8 A	2500	1471	400
CE 68 B	2600	1530	450
L 8 B	2800	1648	450
CE 680 A	2900	1707	500
L 9 A	3100	1825	500
CE 680 B	3200	1883	550
L 9 B	3300	1942	550

TABLE SHOWING CAPACITIES ARE EXPRESSED AS FREE AIR DELIVERY (FAD) WHEN MEASURED IN ACCORDANCE TO ISO 1217: 2009 WITH A NOMINAL PRESSURE OF 35 BAR. MOTOR SERVICE FACTOR = 1.0.

Note: entire range of compressors is designed to operate between 20 & 40 bar pressure.

**Ateliers François SA**  
274 Rue Côte d'Or  
BE-4000 Liège - Belgium

**Head Office Commercial Department:**  
Tel. + 352 26 95 66 34


[Sales@afcompressors.com](mailto:Sales@afcompressors.com)

All contacts worldwide on:

[www.afcompressors.com](http://www.afcompressors.com)



Air Quality according to ISO 8573. Class 2 or 1.4.1. Class 0 compliant.  
Motor service factor = 1.0.  
M, CE, L models, all on anti-vibration mounts.  
Technical modification without prior notice. 2019 06 25.



[WWW.AFCOMPRESSORS.COM](http://WWW.AFCOMPRESSORS.COM)

