

Volufil Series

Features

- Filling range: 200ml to 5 litres & 5 to 15 litres
- Versatile: Minimum adjustment required for setting different capacities.
- Nozzle Type: Diving nozzle with positive cut-off
- Accuracy of Filling: $\pm 0.25\%$ of the filled volume.
- Volume Setting: On HMI with LCD display
- No Container No Fill: Non contact sensors to facilitate "No container no fill" as standard feature.
- Models: Available in 2, 4, 6 & 8 head configuration
- Drip arresting tray below nozzle for accidental drip



Specifications

Volufil 5000 CDD	4X	6X	8X
Machine Speed	Bottles / Containers per hour		
500 ml	1680	2520	2880
1000 ml	1440	2160	2700
2000 ml	1200	1680	1800
5000 ml	720	960	1320
Conveyer Length (mm)	3600	4800	6000
Power (KW)	4.5	5	6
Air Pressure (Kg/sq cm)	5	5	5

Volufil 15000 CDD	4X	6X	8X
Machine Speed	Bottles / Containers per hour		
5 Ltr	720	960	1080
15 Ltr	360	480	600
Conveyer Length (mm)	3600	4800	6000
Power (KW)	4.5	5	6
Air Pressure (Kg/sq cm)	5	5	5

SPANPAK

We fill what flows...

Volufil Series



Spherotech
Packaging India Pvt. Ltd.

📍 201, Gold Crest Business Park, Opp. Shreyas Cinema
L.B.S. Marg, Ghatkopar West, Mumbai 400 086, Maharashtra India.
☎ +91-22-25005773 📞 +91-98330 27390
✉ sales@spherotech.biz
🌐 www.spherotechpackaging.com

